



Last information update: November 2025

Product configuration: 308D.01+RU73.01+RU45.38

308D.01: Linear module - recessed Frame Down - for 1 Li-Fi module and Opal or MPO screen - L=2584 - White

RU73.01: Plate with Warm White LED - Downlight - General Light HO - DALI - L=1196 - 24.5W 2845lm - 3000K - White

RU45.38: Flexible Opal screen L=7,3m - Opaline



Product code

308D.01: Linear module - recessed Frame Down - for 1 Li-Fi module and Opal or MPO screen - L=2584 - White

Technical description

Aluminium extrusion profile, Frame recessed version with trim frame. Prepared for the use of the single or roll screen (for continuous row versions) both Opal and Microprismatic (MPO). The profile has 1 free space of +200 mm which allows the installation of the Smart Li-Fi module.

Installation

Applicable for recessing using the special brackets integrated on the profile.

Colour

White (01)

Wiring

Prepared for housing the LED modules provided by the system and prepared for positioning the Smart Li-Fi module.

Complies with EN60598-1 and pertinent regulations



Product code

RU73.01: Plate with Warm White LED - Downlight - General Light HO - DALI - L=1196 - 24.5W 2845lm - 3000K - White **Attention!**

Code no longer in production

Technical description

Warm White LED plate with direct (Down) light emission. High Output (HO) version for General Light profiles to connect to the relevant Opal screen (single or roll) to be ordered separately. The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables.

Installation

Module insertion on profiles facilitated by a quick coupling system.

Colour

White (01)

Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable DALI power supply.

Complies with EN60598-1 and pertinent regulations



Accessory code

RU45.38: Flexible Opal screen L=7,3m - Opaline

Technical description

Screen with an opal finish L=7,3m used for iN60evo continuous line compositions. Screen locked to aluminium profile via special springs located in the profile.

Installation

The screen is locked via special springs located in the profile.

Colour

Opaline (38)

Weight (Kg)

1.4

Notes

It can be cut and used for different light lines, including opal roll screens
TPa version available on request, contact iGuzzini for more info.

IP20

Technical data

Im system:	5798	Rg (Gamut Index):	95
W system:	49.2	Colour temperature [K]:	3000
Im source:	8920	MacAdam Step:	3
W source:	43	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	117.8	Lamp code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of lamps for optical assembly:	1
Light Output Ratio (L.O.R.) [%]:	65	ZVEI Code:	LED
CRI (minimum):	80	Number of optical assemblies:	1
Rf (Colour Fidelity Index):	85	Control:	DALI-2

Polar