


Last information update: February 2026

Product configuration: SJ93.G0

SJ93.G0: Linear pendant Up/Down luminaire L=1828 - Space Frame optic - UGR<19 - - 19.8W 2706lm - 3000K - CRI 90 - White/White Transparent

**Product code**

SJ93.G0: Linear pendant Up/Down luminaire L=1828 - Space Frame optic - UGR<19 - - 19.8W 2706lm - 3000K - CRI 90 - White/White Transparent

Technical description

Direct (70%) / Indirect (30%) emission luminaire with 3000K CRI90 monochrome LED lamps. Version for UGR < 19 controlled luminance emission - in compliance with the standard for use in environments with video monitors. Opti-Diamond Space optic available with a White (transparent white) or Black Cover (transparent black). Frame version extruded aluminium profile with die-cast zamak end caps. Complete with power and pendant cable L=3000 that can be adjusted as required. Steel pendant mount cable with millimetric adjustment system and brass component. Complete with 48Vdc Mid-Power Led circuit and DALI dimming system. "Powerline" technology allows each product connected to the system to be adjusted separately.

Installation

A tool-free system for connecting the product electrically and mechanically to the 48V Filorail low voltage track.

Colour

White/White Transparent (G0)

Weight (Kg)

1.37

Mounting

ceiling pendant


Wiring

Power supply unit (48V) to be ordered separately as specified in the instruction sheet.

Complies with EN60598-1 and pertinent regulations



IP20

**Technical data**

lm system:	2706	Colour temperature [K]:	3000
W system:	19.8	MacAdam Step:	3
lm source:	3300	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	19	Voltage [Vin]:	48
Luminous efficiency (lm/W, real value):	136.7	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	928	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	82	Number of optical assemblies:	1
CRI (minimum):	90	Power factor:	See installation instructions
Rf (Colour Fidelity Index):	90	Control:	DALI
Rg (Gamut Index):	96		

Polar